




Page	Original Text	Replacement Text	Revision Date																																										
3	PB1230C - PB51156C ... 242	Remove content - Discontinued	03-28-19																																										
3	Incorrect Order No. 2008505	Change to: 2008508	11-05-20																																										
4	Blankets, Protective ... 242 Protective Blankets ... 242	Remove content - Discontinued	03-28-19																																										
15	Ordering Information Table - Column Part No. Errors: 350095 & 350094	Correction: 25750 & 32325, respectively.	04-03-19																																										
	<table border="1"> <thead> <tr> <th>Cylinder Tons</th> <th>Part No.</th> <th>A (in.)</th> <th>B (in.)</th> <th>C (in.)</th> <th>D (in.)</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>350095</td> <td>4.50</td> <td>2.50</td> <td>3/4 - 14 NPSM</td> <td>1.34</td> </tr> <tr> <td>10 or 15*</td> <td>350094</td> <td>.375</td> <td>3.50</td> <td>1 1/4 - 11 1/2 NPSM</td> <td>1.44</td> </tr> </tbody> </table>	Cylinder Tons	Part No.	A (in.)	B (in.)	C (in.)	D (in.)	5	350095	4.50	2.50	3/4 - 14 NPSM	1.34	10 or 15*	350094	.375	3.50	1 1/4 - 11 1/2 NPSM	1.44	<table border="1"> <thead> <tr> <th>Cylinder Tons</th> <th>Part No.</th> <th>A (in.)</th> <th>B (in.)</th> <th>C (in.)</th> <th>D (in.)</th> </tr> </thead> <tbody> <tr> <td>5</td> <td>25750</td> <td>4.50</td> <td>2.50</td> <td>3/4 - 14 NPSM</td> <td>1.34</td> </tr> <tr> <td>10 or 15*</td> <td>32325</td> <td>.375</td> <td>3.50</td> <td>1 1/4 - 11 1/2 NPSM</td> <td>1.44</td> </tr> </tbody> </table>	Cylinder Tons	Part No.	A (in.)	B (in.)	C (in.)	D (in.)	5	25750	4.50	2.50	3/4 - 14 NPSM	1.34	10 or 15*	32325	.375	3.50	1 1/4 - 11 1/2 NPSM	1.44							
Cylinder Tons	Part No.	A (in.)	B (in.)	C (in.)	D (in.)																																								
5	350095	4.50	2.50	3/4 - 14 NPSM	1.34																																								
10 or 15*	350094	.375	3.50	1 1/4 - 11 1/2 NPSM	1.44																																								
Cylinder Tons	Part No.	A (in.)	B (in.)	C (in.)	D (in.)																																								
5	25750	4.50	2.50	3/4 - 14 NPSM	1.34																																								
10 or 15*	32325	.375	3.50	1 1/4 - 11 1/2 NPSM	1.44																																								
34	Technical Dimensions.	Add Notation. † Excludes RD10020.	11-09-20																																										
49	Technical Dimensions. Column J & K, wrong content format and information.		11-19-18																																										
	<table border="1"> <thead> <tr> <th>Order No.</th> <th>J (deg.)</th> <th>K (in.)</th> </tr> </thead> <tbody> <tr> <td>P12</td> <td>45.00</td> <td>0.19</td> </tr> <tr> <td>P19</td> <td>53°</td> <td>5/16</td> </tr> <tr> <td>P23*</td> <td>38.00</td> <td>0.19</td> </tr> <tr> <td>P55</td> <td>38.00</td> <td>0.19</td> </tr> </tbody> </table>	Order No.	J (deg.)	K (in.)	P12	45.00	0.19	P19	53°	5/16	P23*	38.00	0.19	P55	38.00	0.19	<table border="1"> <thead> <tr> <th>Order No.</th> <th>J (deg.)</th> <th>K (in.)</th> </tr> </thead> <tbody> <tr> <td>P12</td> <td>45°</td> <td>0.19</td> </tr> <tr> <td>P19</td> <td>53°</td> <td>0.31</td> </tr> <tr> <td>P23*</td> <td>38°</td> <td>0.31</td> </tr> <tr> <td>P55</td> <td>38°</td> <td>0.31</td> </tr> </tbody> </table>	Order No.	J (deg.)	K (in.)	P12	45°	0.19	P19	53°	0.31	P23*	38°	0.31	P55	38°	0.31													
Order No.	J (deg.)	K (in.)																																											
P12	45.00	0.19																																											
P19	53°	5/16																																											
P23*	38.00	0.19																																											
P55	38.00	0.19																																											
Order No.	J (deg.)	K (in.)																																											
P12	45°	0.19																																											
P19	53°	0.31																																											
P23*	38°	0.31																																											
P55	38°	0.31																																											
49	Technical Dimensions: Missing P59 & P59F	Add P59 & P59F	11-19-18																																										
		<table border="1"> <thead> <tr> <th>Order No.</th> <th>A (in.)</th> <th>B (in.)</th> <th>C (in.)</th> <th>D (in.)</th> <th>E (in.)</th> <th>F (in.)</th> </tr> </thead> <tbody> <tr> <td>P59</td> <td>7.00</td> <td>21.00</td> <td>3.50</td> <td>5.00</td> <td>23.00</td> <td>4.25</td> </tr> <tr> <td>P59F</td> <td>3.50</td> <td>16.75</td> <td>3.50</td> <td>6.00</td> <td>23.25</td> <td>4.25</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>G (in.)</th> <th>H (in.)</th> <th>J (deg.)</th> <th>K (in.)</th> <th>L (in.)</th> <th>M (in.)</th> <th>N (in.)</th> </tr> </thead> <tbody> <tr> <td>3.25</td> <td>19.75</td> <td>38°</td> <td>0.31</td> <td>4.75</td> <td>3/8 NPTF</td> <td>1.63</td> </tr> <tr> <td>3.25</td> <td>20.25</td> <td>—</td> <td>0.31</td> <td>4.50</td> <td>3/8 NPTF</td> <td>1.69</td> </tr> </tbody> </table>	Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	P59	7.00	21.00	3.50	5.00	23.00	4.25	P59F	3.50	16.75	3.50	6.00	23.25	4.25	G (in.)	H (in.)	J (deg.)	K (in.)	L (in.)	M (in.)	N (in.)	3.25	19.75	38°	0.31	4.75	3/8 NPTF	1.63	3.25	20.25	—	0.31	4.50	3/8 NPTF	1.69	
Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)																																							
P59	7.00	21.00	3.50	5.00	23.00	4.25																																							
P59F	3.50	16.75	3.50	6.00	23.25	4.25																																							
G (in.)	H (in.)	J (deg.)	K (in.)	L (in.)	M (in.)	N (in.)																																							
3.25	19.75	38°	0.31	4.75	3/8 NPTF	1.63																																							
3.25	20.25	—	0.31	4.50	3/8 NPTF	1.69																																							
49	Ordering Information: Missing P59 & P59F	Add P59 & P59F	11-19-18																																										
		<table border="1"> <thead> <tr> <th rowspan="2">For Use With</th> <th rowspan="2">Speed</th> <th rowspan="2">Order No.</th> <th colspan="2">Volume per Stroke</th> <th colspan="2">Max. Pressure</th> </tr> <tr> <th>LP (cu. in.)</th> <th>HP (cu. in.)</th> <th>LP (psi)</th> <th>HP (psi)</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Single-Acting Cylinders</td> <td>2</td> <td>P59</td> <td>0.662</td> <td>0.160</td> <td>325</td> <td>10,000</td> </tr> <tr> <td>2</td> <td>P59F</td> <td>0.550</td> <td>0.130</td> <td>325</td> <td>10,000</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th rowspan="2">Handle Effort (lbs.)</th> <th colspan="2">Reservoir</th> <th rowspan="2">Oil Port (in.)</th> <th rowspan="2">Prod. Wt. (lbs.)</th> </tr> <tr> <th>Oil Cap. (cu. in.)</th> <th>Usable Oil Cap. (cu. in.)</th> </tr> </thead> <tbody> <tr> <td>145</td> <td>55.00</td> <td>45.00</td> <td>3/8 NPTF</td> <td>17.20</td> </tr> <tr> <td>120</td> <td>55.00</td> <td>45.00</td> <td>3/8 NPTF</td> <td>14.00</td> </tr> </tbody> </table>	For Use With	Speed	Order No.	Volume per Stroke		Max. Pressure		LP (cu. in.)	HP (cu. in.)	LP (psi)	HP (psi)	Single-Acting Cylinders	2	P59	0.662	0.160	325	10,000	2	P59F	0.550	0.130	325	10,000	Handle Effort (lbs.)	Reservoir		Oil Port (in.)	Prod. Wt. (lbs.)	Oil Cap. (cu. in.)	Usable Oil Cap. (cu. in.)	145	55.00	45.00	3/8 NPTF	17.20	120	55.00	45.00	3/8 NPTF	14.00		
For Use With	Speed	Order No.				Volume per Stroke		Max. Pressure																																					
			LP (cu. in.)	HP (cu. in.)	LP (psi)	HP (psi)																																							
Single-Acting Cylinders	2	P59	0.662	0.160	325	10,000																																							
	2	P59F	0.550	0.130	325	10,000																																							
Handle Effort (lbs.)	Reservoir		Oil Port (in.)	Prod. Wt. (lbs.)																																									
	Oil Cap. (cu. in.)	Usable Oil Cap. (cu. in.)																																											
145	55.00	45.00	3/8 NPTF	17.20																																									
120	55.00	45.00	3/8 NPTF	14.00																																									
50	Technical Dimensions. Missing two notations.	Technical Dimensions. Add two notations. * Overall length, with the skid plate, is 28.30 in. (718.8 mm.). ** High pressure 60° cone port.	11-15-18																																										
67	Features.	Remove the following text.  "Usable in hazardous area (per ATEX II, CAT. 2 GDcT5)."	08-14-20																																										
71-72	Page Header - 70 CU. IN / MIN.	Page Header - 70 CU. IN.	11-08-18																																										

Page	Original Text	Replacement Text	Revision Date																																																																																																																																																																	
	Table - Ordering Information.	Update Table Description, Valve Type & Function. Add New Product: "PB102-CP" Add (5) Notation.	7-15-2020																																																																																																																																																																	
72	Table - Column "Battery Included" Error: 18VDC L-ion 9.0 Ah	Correction: 18VDC Li-on 9.0 Ah	11-08-18																																																																																																																																																																	
72	Table - Column "A - Length" Error: 12.81 inches	Correction: 17.23 inches	09-11-20																																																																																																																																																																	
88	Table. Row - "PE550-RP50", Column - "Description". Error: ", & 3 way valve."	Correction: Remove ", & 3 way valve."	04-08-19																																																																																																																																																																	
115	Table. Row - 9520. Inforrect: Column - "Valve Type". Error: "4-Way; 3-Post. Tandem Center"	Correction: "3-Way; 3-Post. Tandem Center"	07-16-20																																																																																																																																																																	
124	Notation: <b>IMPORTANT:</b> When ordering any valve for a PE30 or PG30 series pump, 1/2" longer mounting screws are required. For valves 9569, 9570 and 9579, order four 10856 cap screws. For valves 9552, 9572 and 9592, order four 12001 cap screws."	Remove last sentence: "For valve 9576, order four 17428 cap screws."	11-15-18																																																																																																																																																																	
142	Technical Attribute, No. 7. Add a notation.	* High pressure 60° cone port.	11-15-18																																																																																																																																																																	
144	<b>2-Port Manifold.</b> Manifold with four needle valves for control of four cylinders. Has six 3/8" NPTF ports. Wt. 16.2 lbs.	<b>4-Port Manifold.</b> Manifold with four needle valves for control of four cylinders. Has six 3/8" NPTF ports. Wt. 16.2 lbs.	4-30-20																																																																																																																																																																	
178	Order Information Table - Row: IJ4516T. Incorrect Length & Width. Error: 38.00	Length & Width. Correction: 28.00	3-20-20																																																																																																																																																																	
	<table border="1"> <thead> <tr> <th>Order Number</th> <th>Lifting Cap. (lbs.)</th> <th>Lifting Height (in.)</th> <th>Air Volume (cu. ft.)</th> <th>Water Volume (gal.)</th> <th>Length (in.)</th> <th>Width (in.)</th> <th>Thickness (in.)</th> <th>Prod. Wt. (lbs.)</th> </tr> </thead> <tbody> <tr><td>IJ10T</td><td>2240</td><td>3.1</td><td>0.52</td><td>0.18</td><td>4.00</td><td>6.50</td><td>0.87</td><td>1.30</td></tr> <tr><td>IJ40T</td><td>7194</td><td>5.1</td><td>0.57</td><td>0.68</td><td>9.00</td><td>9.30</td><td>0.87</td><td>3.30</td></tr> <tr><td>IJ6T</td><td>11243</td><td>5.9</td><td>0.80</td><td>0.66</td><td>11.00</td><td>11.00</td><td>0.87</td><td>4.40</td></tr> <tr><td>IJ110T</td><td>22480</td><td>8.5</td><td>2.70</td><td>2.24</td><td>15.00</td><td>15.00</td><td>0.98</td><td>9.00</td></tr> <tr><td>IJ2211T</td><td>44960</td><td>11.4</td><td>6.67</td><td>5.65</td><td>20.00</td><td>20.00</td><td>0.98</td><td>15.50</td></tr> <tr><td>LJ3010T</td><td>71930</td><td>15.0</td><td>15.89</td><td>13.00</td><td>26.00</td><td>26.00</td><td>0.98</td><td>29.00</td></tr> <tr><td>IJ4516T*</td><td>85930</td><td>15.9</td><td>19.73</td><td>16.38</td><td>30.00</td><td>30.00</td><td>0.98</td><td>33.00</td></tr> <tr><td>IJ7520T*</td><td>150810</td><td>20.5</td><td>42.59</td><td>36.40</td><td>36.00</td><td>36.00</td><td>0.98</td><td>53.00</td></tr> </tbody> </table>	Order Number	Lifting Cap. (lbs.)	Lifting Height (in.)	Air Volume (cu. ft.)	Water Volume (gal.)	Length (in.)	Width (in.)	Thickness (in.)	Prod. Wt. (lbs.)	IJ10T	2240	3.1	0.52	0.18	4.00	6.50	0.87	1.30	IJ40T	7194	5.1	0.57	0.68	9.00	9.30	0.87	3.30	IJ6T	11243	5.9	0.80	0.66	11.00	11.00	0.87	4.40	IJ110T	22480	8.5	2.70	2.24	15.00	15.00	0.98	9.00	IJ2211T	44960	11.4	6.67	5.65	20.00	20.00	0.98	15.50	LJ3010T	71930	15.0	15.89	13.00	26.00	26.00	0.98	29.00	IJ4516T*	85930	15.9	19.73	16.38	30.00	30.00	0.98	33.00	IJ7520T*	150810	20.5	42.59	36.40	36.00	36.00	0.98	53.00	<table border="1"> <thead> <tr> <th>Order Number</th> <th>Lifting Cap. (lbs.)</th> <th>Lifting Height (in.)</th> <th>Air Volume (cu. ft.)</th> <th>Water Volume (gal.)</th> <th>Length (in.)</th> <th>Width (in.)</th> <th>Thickness (in.)</th> <th>Prod. Wt. (lbs.)</th> </tr> </thead> <tbody> <tr><td>IJ10T</td><td>2240</td><td>3.1</td><td>0.52</td><td>0.18</td><td>4.00</td><td>6.50</td><td>0.87</td><td>1.30</td></tr> <tr><td>IJ40T</td><td>7194</td><td>5.1</td><td>0.57</td><td>0.68</td><td>9.00</td><td>9.30</td><td>0.87</td><td>3.30</td></tr> <tr><td>IJ6T</td><td>11243</td><td>5.9</td><td>0.80</td><td>0.66</td><td>11.00</td><td>11.00</td><td>0.87</td><td>4.40</td></tr> <tr><td>IJ110T</td><td>22480</td><td>8.5</td><td>2.70</td><td>2.24</td><td>15.00</td><td>15.00</td><td>0.98</td><td>9.00</td></tr> <tr><td>IJ2211T</td><td>44960</td><td>11.4</td><td>6.67</td><td>5.65</td><td>20.00</td><td>20.00</td><td>0.98</td><td>15.50</td></tr> <tr><td>IJ4516T*</td><td>71930</td><td>15.0</td><td>15.89</td><td>13.00</td><td>26.00</td><td>26.00</td><td>0.98</td><td>29.00</td></tr> <tr><td>IJ4516T*</td><td>85930</td><td>15.9</td><td>19.73</td><td>16.38</td><td>30.00</td><td>30.00</td><td>0.98</td><td>33.00</td></tr> <tr><td>IJ7520T*</td><td>150810</td><td>20.5</td><td>42.59</td><td>36.40</td><td>36.00</td><td>36.00</td><td>0.98</td><td>53.00</td></tr> </tbody> </table>	Order Number	Lifting Cap. (lbs.)	Lifting Height (in.)	Air Volume (cu. ft.)	Water Volume (gal.)	Length (in.)	Width (in.)	Thickness (in.)	Prod. Wt. (lbs.)	IJ10T	2240	3.1	0.52	0.18	4.00	6.50	0.87	1.30	IJ40T	7194	5.1	0.57	0.68	9.00	9.30	0.87	3.30	IJ6T	11243	5.9	0.80	0.66	11.00	11.00	0.87	4.40	IJ110T	22480	8.5	2.70	2.24	15.00	15.00	0.98	9.00	IJ2211T	44960	11.4	6.67	5.65	20.00	20.00	0.98	15.50	IJ4516T*	71930	15.0	15.89	13.00	26.00	26.00	0.98	29.00	IJ4516T*	85930	15.9	19.73	16.38	30.00	30.00	0.98	33.00	IJ7520T*	150810	20.5	42.59	36.40	36.00	36.00	0.98	53.00
Order Number	Lifting Cap. (lbs.)	Lifting Height (in.)	Air Volume (cu. ft.)	Water Volume (gal.)	Length (in.)	Width (in.)	Thickness (in.)	Prod. Wt. (lbs.)																																																																																																																																																												
IJ10T	2240	3.1	0.52	0.18	4.00	6.50	0.87	1.30																																																																																																																																																												
IJ40T	7194	5.1	0.57	0.68	9.00	9.30	0.87	3.30																																																																																																																																																												
IJ6T	11243	5.9	0.80	0.66	11.00	11.00	0.87	4.40																																																																																																																																																												
IJ110T	22480	8.5	2.70	2.24	15.00	15.00	0.98	9.00																																																																																																																																																												
IJ2211T	44960	11.4	6.67	5.65	20.00	20.00	0.98	15.50																																																																																																																																																												
LJ3010T	71930	15.0	15.89	13.00	26.00	26.00	0.98	29.00																																																																																																																																																												
IJ4516T*	85930	15.9	19.73	16.38	30.00	30.00	0.98	33.00																																																																																																																																																												
IJ7520T*	150810	20.5	42.59	36.40	36.00	36.00	0.98	53.00																																																																																																																																																												
Order Number	Lifting Cap. (lbs.)	Lifting Height (in.)	Air Volume (cu. ft.)	Water Volume (gal.)	Length (in.)	Width (in.)	Thickness (in.)	Prod. Wt. (lbs.)																																																																																																																																																												
IJ10T	2240	3.1	0.52	0.18	4.00	6.50	0.87	1.30																																																																																																																																																												
IJ40T	7194	5.1	0.57	0.68	9.00	9.30	0.87	3.30																																																																																																																																																												
IJ6T	11243	5.9	0.80	0.66	11.00	11.00	0.87	4.40																																																																																																																																																												
IJ110T	22480	8.5	2.70	2.24	15.00	15.00	0.98	9.00																																																																																																																																																												
IJ2211T	44960	11.4	6.67	5.65	20.00	20.00	0.98	15.50																																																																																																																																																												
IJ4516T*	71930	15.0	15.89	13.00	26.00	26.00	0.98	29.00																																																																																																																																																												
IJ4516T*	85930	15.9	19.73	16.38	30.00	30.00	0.98	33.00																																																																																																																																																												
IJ7520T*	150810	20.5	42.59	36.40	36.00	36.00	0.98	53.00																																																																																																																																																												
180	Features. Remove the following text.  "Set IM10H/IM10L includes hand operated pump. Set IM10E includes the Quarter Horse® electrically driven portable power unit."	Features. Replace the following text.  The IM10B comes with a battery powered pump, while the IM10E comes with an electric pump. Both come with two 10T cylinders. The IM10P/IM10L come with hand pumps and one 10T cylinder.	5-15-20																																																																																																																																																																	
180		Order Information Table. Add new product: IM10B	5-15-20																																																																																																																																																																	
201	New Product: TWSL Torque Wrench.	Technical Dimensions. Add TWSL2 Content	04-03-19																																																																																																																																																																	
	<table border="1"> <thead> <tr> <th>Order No.</th> <th>A (in.)</th> <th>B (in.)</th> <th>C (in.)</th> <th>D (in.)</th> <th>E (in.)</th> <th>F (in.)</th> <th>G (in.)</th> </tr> </thead> <tbody> <tr><td>TWSL1</td><td>6.61</td><td>5.39</td><td>6.61</td><td>6.61</td><td>0.42</td><td>1.20</td><td>2.04</td></tr> </tbody> </table>	Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)	TWSL1	6.61	5.39	6.61	6.61	0.42	1.20	2.04	<table border="1"> <thead> <tr> <th>Order No.</th> <th>A (in.)</th> <th>B (in.)</th> <th>C (in.)</th> <th>D (in.)</th> <th>E (in.)</th> <th>F (in.)</th> <th>G (in.)</th> </tr> </thead> <tbody> <tr><td>TWSL2</td><td>5.71</td><td>4.48</td><td>5.04</td><td>7.26</td><td>0.35</td><td>0.98</td><td>1.65</td></tr> <tr><td>TWSL4</td><td>6.61</td><td>5.39</td><td>6.61</td><td>6.61</td><td>0.42</td><td>1.20</td><td>2.04</td></tr> </tbody> </table>	Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)	TWSL2	5.71	4.48	5.04	7.26	0.35	0.98	1.65	TWSL4	6.61	5.39	6.61	6.61	0.42	1.20	2.04																																																																																																																										
Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)																																																																																																																																																													
TWSL1	6.61	5.39	6.61	6.61	0.42	1.20	2.04																																																																																																																																																													
Order No.	A (in.)	B (in.)	C (in.)	D (in.)	E (in.)	F (in.)	G (in.)																																																																																																																																																													
TWSL2	5.71	4.48	5.04	7.26	0.35	0.98	1.65																																																																																																																																																													
TWSL4	6.61	5.39	6.61	6.61	0.42	1.20	2.04																																																																																																																																																													

Page	Original Text	Replacement Text	Revision Date																																																						
201 & 202	<p>New Product: TWSL2 Torque Wrench Revised: Info Boxes.</p> <p><i>Optional Handle</i> Order #: DFTAS000002</p>	<p>Add TWSL2, Modify DFTAS000002 Content</p> <p><i>Optional Handle</i> Order #: DFTAS000001 for TWSL2 DFTAS000002 for TWSL4</p>	04-03-19																																																						
202	<p>New Product. TWSL2 Torque Wrench Revised: Torque Wrench Drive Body Order Info.</p> <table border="1"> <thead> <tr> <th>Drive Body Order No.</th> <th colspan="2">Hex Range for SlimLine</th> <th>SlimLine Min. Torque</th> <th>SlimLine Max. Torque</th> <th>Weight (Link Only)</th> </tr> <tr> <th></th> <th>(in.)</th> <th>(in.)</th> <th>(ft. lbs.)</th> <th>(ft. lbs.)</th> <th>(lbs.)</th> </tr> </thead> <tbody> <tr> <td>TWLC2</td> <td>1.13</td> <td>2.38</td> <td colspan="2">Contact Factory for Details</td> <td>2.2</td> </tr> <tr> <td>TWLC4</td> <td>1.81</td> <td>3.13</td> <td>505</td> <td>2,539 - 4,210</td> <td>4.4</td> </tr> <tr> <td>TWLC8</td> <td>2.25</td> <td>3.94</td> <td colspan="2">Contact Factory for Details</td> <td>7.7</td> </tr> </tbody> </table>	Drive Body Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)		(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)	TWLC2	1.13	2.38	Contact Factory for Details		2.2	TWLC4	1.81	3.13	505	2,539 - 4,210	4.4	TWLC8	2.25	3.94	Contact Factory for Details		7.7	<p>Add TWSL2 Content. Remove TWSL8.</p> <table border="1"> <thead> <tr> <th>Drive Body Order No.</th> <th colspan="2">Hex Range for SlimLine</th> <th>SlimLine Min. Torque</th> <th>SlimLine Max. Torque</th> <th>Weight (Link Only)</th> </tr> <tr> <th></th> <th>(in.)</th> <th>(in.)</th> <th>(ft. lbs.)</th> <th>(ft. lbs.)</th> <th>(lbs.)</th> </tr> </thead> <tbody> <tr> <td>TWLC2</td> <td>1.13</td> <td>2.38</td> <td>222</td> <td>1,240 - 1,850</td> <td>2.2</td> </tr> <tr> <td>TWLC4</td> <td>1.81</td> <td>3.13</td> <td>505</td> <td>2,639 - 4,210</td> <td>4.4</td> </tr> </tbody> </table>	Drive Body Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)		(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)	TWLC2	1.13	2.38	222	1,240 - 1,850	2.2	TWLC4	1.81	3.13	505	2,639 - 4,210	4.4	04-03-19
Drive Body Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)																																																				
	(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)																																																				
TWLC2	1.13	2.38	Contact Factory for Details		2.2																																																				
TWLC4	1.81	3.13	505	2,539 - 4,210	4.4																																																				
TWLC8	2.25	3.94	Contact Factory for Details		7.7																																																				
Drive Body Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)																																																				
	(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)																																																				
TWLC2	1.13	2.38	222	1,240 - 1,850	2.2																																																				
TWLC4	1.81	3.13	505	2,639 - 4,210	4.4																																																				
202	<p>New Product: TWSL2 Torque Wrench Revised: Torque Wrench Link Order Info.</p> <table border="1"> <thead> <tr> <th>Link Order No.</th> <th colspan="2">Hex Range for SlimLine</th> <th>SlimLine Min. Torque</th> <th>SlimLine Max. Torque</th> <th>Weight (Link Only)</th> </tr> <tr> <th></th> <th>(in.)</th> <th>(in.)</th> <th>(ft. lbs.)</th> <th>(ft. lbs.)</th> <th>(lbs.)</th> </tr> </thead> <tbody> <tr> <td>TWSL2-F</td> <td>1.13</td> <td>2.38</td> <td colspan="2">Contact Factory for Details</td> <td></td> </tr> <tr> <td>TWSL4-F</td> <td>1.81</td> <td>3.13</td> <td>505</td> <td>2,539 - 4,210</td> <td>8.0 - 8.4</td> </tr> <tr> <td>TWSL8-F</td> <td>2.25</td> <td>3.94</td> <td colspan="2">Contact Factory for Details</td> <td></td> </tr> </tbody> </table>	Link Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)		(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)	TWSL2-F	1.13	2.38	Contact Factory for Details			TWSL4-F	1.81	3.13	505	2,539 - 4,210	8.0 - 8.4	TWSL8-F	2.25	3.94	Contact Factory for Details			<p>Add TWSL2 Content. Remove TWSL8.</p> <table border="1"> <thead> <tr> <th>Link Order No.</th> <th colspan="2">Hex Range for SlimLine</th> <th>SlimLine Min. Torque</th> <th>SlimLine Max. Torque</th> <th>Weight (Link Only)</th> </tr> <tr> <th></th> <th>(in.)</th> <th>(in.)</th> <th>(ft. lbs.)</th> <th>(ft. lbs.)</th> <th>(lbs.)</th> </tr> </thead> <tbody> <tr> <td>TWSL2-F</td> <td>1.13</td> <td>2.38</td> <td>222</td> <td>1,240 - 1,850</td> <td>4.2 - 4.5</td> </tr> <tr> <td>TWSL4-F</td> <td>1.81</td> <td>3.13</td> <td>505</td> <td>2,639 - 4,210</td> <td>8.0 - 8.4</td> </tr> </tbody> </table>	Link Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)		(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)	TWSL2-F	1.13	2.38	222	1,240 - 1,850	4.2 - 4.5	TWSL4-F	1.81	3.13	505	2,639 - 4,210	8.0 - 8.4	04-03-19
Link Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)																																																				
	(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)																																																				
TWSL2-F	1.13	2.38	Contact Factory for Details																																																						
TWSL4-F	1.81	3.13	505	2,539 - 4,210	8.0 - 8.4																																																				
TWSL8-F	2.25	3.94	Contact Factory for Details																																																						
Link Order No.	Hex Range for SlimLine		SlimLine Min. Torque	SlimLine Max. Torque	Weight (Link Only)																																																				
	(in.)	(in.)	(ft. lbs.)	(ft. lbs.)	(lbs.)																																																				
TWSL2-F	1.13	2.38	222	1,240 - 1,850	4.2 - 4.5																																																				
TWSL4-F	1.81	3.13	505	2,639 - 4,210	8.0 - 8.4																																																				
202	<p>New Product: TWSL2 Torque Wrench</p>	<p>Add TWSL2 SlimLine Link Reference Table</p> <p>► <b>TWSL2 SlimLine Link Reference Table*</b></p> <table border="1"> <thead> <tr> <th>Nut A/F</th> <th>Link Order No.</th> <th>Max. Torque</th> <th>Weight (Link Only)</th> </tr> <tr> <th>(in.)</th> <th></th> <th>(ft. lbs.)</th> <th>(lbs.)</th> </tr> </thead> <tbody> <tr> <td>1.25</td> <td>TWSL2-032</td> <td>1,240</td> <td>4.1</td> </tr> <tr> <td>1.44</td> <td>TWSL2-036</td> <td>1,430</td> <td>4.2</td> </tr> <tr> <td>1.63</td> <td>TWSL2-041</td> <td>1,600</td> <td>4.3</td> </tr> <tr> <td>1.81</td> <td>TWSL2-046</td> <td>1,850</td> <td>4.3</td> </tr> <tr> <td>2.00</td> <td>TWSL2-050</td> <td>1,850</td> <td>4.3</td> </tr> <tr> <td>2.19</td> <td>TWSL2-055</td> <td>1,850</td> <td>4.4</td> </tr> <tr> <td>2.38</td> <td>TWSL2-060</td> <td>1,850</td> <td>4.4</td> </tr> </tbody> </table>	Nut A/F	Link Order No.	Max. Torque	Weight (Link Only)	(in.)		(ft. lbs.)	(lbs.)	1.25	TWSL2-032	1,240	4.1	1.44	TWSL2-036	1,430	4.2	1.63	TWSL2-041	1,600	4.3	1.81	TWSL2-046	1,850	4.3	2.00	TWSL2-050	1,850	4.3	2.19	TWSL2-055	1,850	4.4	2.38	TWSL2-060	1,850	4.4	04-03-19																		
Nut A/F	Link Order No.	Max. Torque	Weight (Link Only)																																																						
(in.)		(ft. lbs.)	(lbs.)																																																						
1.25	TWSL2-032	1,240	4.1																																																						
1.44	TWSL2-036	1,430	4.2																																																						
1.63	TWSL2-041	1,600	4.3																																																						
1.81	TWSL2-046	1,850	4.3																																																						
2.00	TWSL2-050	1,850	4.3																																																						
2.19	TWSL2-055	1,850	4.4																																																						
2.38	TWSL2-060	1,850	4.4																																																						
217	<p>Product Discontinued: Hydraulic Tools: HT50A</p>	<p>Remove image and Order No. content.</p>	07-17-20																																																						
242	<p>Product Discontinued: Puller Accessories - "Protective Blanket"</p> <table border="1"> <thead> <tr> <th>Order No.</th> <th>Size (in.)</th> <th>Number of Straps</th> <th>Weight (lbs.)</th> </tr> </thead> <tbody> <tr> <td>PB1230C</td> <td>12 x 30</td> <td>2</td> <td>2.80</td> </tr> <tr> <td>PB2036C</td> <td>20 x 36</td> <td>2</td> <td>4.20</td> </tr> <tr> <td>PB2860C</td> <td>28 x 60</td> <td>3</td> <td>9.30</td> </tr> <tr> <td>PB3372C</td> <td>33 x 72</td> <td>3</td> <td>11.70</td> </tr> <tr> <td>PB44120C</td> <td>44 x 120</td> <td>4</td> <td>24.20</td> </tr> <tr> <td>PB51156C</td> <td>51 x 156</td> <td>4</td> <td>34.40</td> </tr> </tbody> </table>	Order No.	Size (in.)	Number of Straps	Weight (lbs.)	PB1230C	12 x 30	2	2.80	PB2036C	20 x 36	2	4.20	PB2860C	28 x 60	3	9.30	PB3372C	33 x 72	3	11.70	PB44120C	44 x 120	4	24.20	PB51156C	51 x 156	4	34.40	<p>Remove image and Order No. content</p>	03-28-19																										
Order No.	Size (in.)	Number of Straps	Weight (lbs.)																																																						
PB1230C	12 x 30	2	2.80																																																						
PB2036C	20 x 36	2	4.20																																																						
PB2860C	28 x 60	3	9.30																																																						
PB3372C	33 x 72	3	11.70																																																						
PB44120C	44 x 120	4	24.20																																																						
PB51156C	51 x 156	4	34.40																																																						

Page	Original Text	Replacement Text	Revision Date						
245	<p>Puller Accessories - "Hydraulic Lift Cart" Discontinued</p>  <p>Hydraulic Lift Cart</p> <table border="1" data-bbox="459 436 737 655"> <thead> <tr> <th>Order No.</th> </tr> </thead> <tbody> <tr> <td>Hydraulic Lift Cart</td> </tr> <tr> <td>PTPT-3050</td> </tr> <tr> <td>PTPT-3050</td> </tr> <tr> <td>PTPT-3050</td> </tr> <tr> <td>PTPT-3050</td> </tr> </tbody> </table>	Order No.	Hydraulic Lift Cart	PTPT-3050	PTPT-3050	PTPT-3050	PTPT-3050	Remove image and Order No. content	11-08-18
Order No.									
Hydraulic Lift Cart									
PTPT-3050									
PTPT-3050									
PTPT-3050									
PTPT-3050									
246	Table. Incorrect Order No. 2008505	Change to: 2008508	11-05-20						
259	Ordering Information Table - Column Order No. Error: PH553CL	Correction: PH553CL13	11-15-18						
260	Ordering Information Table - Column Order No. Error: PH553C & PH553C13	Correction: PH1002 & PH1002J	11-08-18						
260	Ram Extensions - Order No. Errors: 251002, 350594, & 350637	Corrections: 44745, 44766, 303045.	10-02-19						
279	Table - Cylinder Seal Kits. For Order Numbers: R5652D, R5656D, and R56510D, Column Seal Kit: Error "300934"	Correction: 300681	11-13-18						
Back Cover	<p>Old Address: <b>Australia Headquarters</b> Level 2, Quad 2, 6 Parkview Dr. Sydney Olympic Park, NSW 2127 Australia Tel: +61 3 9589 9222</p>	<p>New Address: <b>Australia Headquarters</b> SPX Flow Technology Australia Pty Ltd Quad 2, 6 Parkview Drive Homebush Bay NSW 2127 Tel: +61 02 9763 4900 Fax: +61 02 9763 7888 Ft.aus.cs@spxflow.com</p>	03-22-19						
Back Cover	Add New Location	<p><b>India Headquarters</b> SPX Flow Technology (India) Pvt. Limited Survey No. 275 Odhav, Ahmedabad - 382 415 Tel: +91-99099-85454 +91-97277-19950 india@powerteam.com</p>	03-22-19						

# SPXFLOW

## GLOBAL CUSTOMER SERVICE CENTERS

### North America Headquarters

5885 11th Street  
Rockford, IL 61109  
USA

#### Customer Service/Order Entry

Tel: +1 800 541 1418  
Fax: +1 800 288 7031

Send P.O's to: [info@powerteam.com](mailto:info@powerteam.com)

#### Technical Services

Tel: +1 800 477 8326  
Fax: +1 800 765 8326

### European Headquarters

Albert Thijsstraat 12  
6471 WX Eyselshoven  
The Netherlands  
Tel: +31 45 567 8877

[infoeurope@powerteam.com](mailto:infoeurope@powerteam.com)

### SEA Headquarters

20 Pioneer Crescent #06-01  
West Park BizCentral  
Singapore 628555  
Tel: +65 6264 4366  
Fax: +65 6265 9133

[infoasia@powerteam.com](mailto:infoasia@powerteam.com)

### India Headquarters

SPX Flow Technology (India) Pvt. Limited  
Survey No. 275  
Odhav, Ahmedabad - 382 415  
Tel: +91-99099-85454  
+91-97277-19950

[india@powerteam.com](mailto:india@powerteam.com)

### China Headquarters

7F Treasury Building  
1568 Huashan Road  
Shanghai, 200052 China  
Tel: +86 21 2208 5888  
Fax: +86 21 2208 5682

[infochina@powerteam.com](mailto:infochina@powerteam.com)

### Australia Headquarters

SPX Flow Technology Australia Pty Ltd  
Quad 2, 6 Parkview Drive  
Homebush Bay NSW 2127  
Tel: +61 02 9763 4900  
Fax: +61 02 9763 7888

[Ft.aus.cs@spxflow.com](mailto:Ft.aus.cs@spxflow.com)

Visit us at [powerteam.com](http://powerteam.com) to learn more.



## >Power Team®

SPX FLOW, Inc. reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing. Please contact your local sales representative for product availability in your region. For more information visit [www.spxflow.com](http://www.spxflow.com).

The green ">" and "X" are trademarks of SPX FLOW, Inc.

Bulletin: PT1901 Version: 09/2020

COPYRIGHT © 2020 SPX FLOW INC.